

Safety Data Sheet

Issue Date: 04-Dec-2004

Revision Date: 13-Jul-2018

Version 2

1. IDENTIFICATION

Product Identifier

Product Name Plastpro Fiberglass Doors

Other means of identification

SDS # PLASTPRO-001

Recommended use of the chemical and restrictions on use

Recommended Use Door.

Details of the supplier of the safety data sheet

Manufacturer Address

Plastpro, Inc.
4737 Kister Court
Ashtabula, OH 44004

Emergency Telephone Number

Company Phone Number 440-969-9773

Emergency Telephone (24 hr) 440-969-9773

2. HAZARDS IDENTIFICATION

Physical state Solid

Odor No odor

Classification

According to 29 CFR 1910.1200, this product meets the definition of an "article".

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1

Signal Word

Danger

Hazard statements

Harmful if inhaled
Causes skin irritation
Causes serious eye irritation
May cause cancer
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 Take off contaminated clothing and wash it before reuse
 If skin irritation occurs: Get medical advice/attention
 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER or doctor

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Calcium Carbonate	1317-65-3	30-40
Wood Dust Particles	9004-34-6	10-20
Fiberglass (Fibrous Glass)	65997-17-3	10-20
Styrene	100-42-5	10-20
Zinc Stearate	557-05-1	<1
Titanium(IV) Oxide	13463-67-7	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice	The information below applies to manufacturing and processing of the product.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.
Skin Contact	Wash with soap and water.
Inhalation	Remove to fresh air. Call a physician.
Ingestion	Do NOT induce vomiting. Call a physician.

Most important symptoms and effects**Symptoms**

May be harmful if swallowed. May be harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Dry chemical. Carbon dioxide (CO₂). Foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal Precautions**

Use personal protective equipment as required.

Environmental precautions**Environmental precautions**

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up

Collect and reuse if possible.

7. HANDLING AND STORAGE

Precautions for safe handling**Advice on Safe Handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep in a dry, cool and well-ventilated place.

Incompatible Materials

None.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Wood Dust Particles 9004-34-6	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ (vacated) STEL: 10 mg/m ³	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 1 mg/m ³
Fiberglass (Fibrous Glass) 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable particulate matter	-	-
Styrene 100-42-5	STEL: 40 ppm TWA: 20 ppm	TWA: 100 ppm (vacated) TWA: 50 ppm (vacated) TWA: 215 mg/m ³ (vacated) STEL: 100 ppm (vacated) STEL: 425 mg/m ³ (vacated) Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m ³ STEL: 100 ppm STEL: 425 mg/m ³
Calcium stearate 1592-23-0	TWA: 10 mg/m ³ inhalable particulate matter except stearates of toxic metals TWA: 3 mg/m ³ respirable particulate matter except stearates of toxic metals	-	-
Zinc Stearate 557-05-1	TWA: 10 mg/m ³ inhalable particulate matter TWA: 3 mg/m ³ respirable particulate matter TWA: 10 mg/m ³ inhalable particulate matter except stearates of toxic metals TWA: 3 mg/m ³ respirable particulate matter except stearates of toxic metals	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium(IV) Oxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³

Appropriate engineering controls

Engineering Controls Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles).

Skin and Body Protection Protective gloves should be worn.

Respiratory Protection Not normally required. Provide ventilation to control dust levels to below exposure limits.

General Hygiene Considerations Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Solid	Odor	No odor
Appearance	Not determined	Odor Threshold	Not determined
Color	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting point / freezing point	Not applicable	
Boiling Point / Boiling Range	Not applicable	
Flash Point	361 °C / 682 °F	
Evaporation Rate	Not applicable	
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper Flammability Limit	Not applicable	
Lower Flammability Limit	Not applicable	
Vapor Pressure	Not applicable	
Vapor Density	Not applicable	
Relative Density	0.35	
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Excessive heat. Ignition sources.

Incompatible Materials

None.

Hazardous Decomposition Products

Carbon oxides. Hydrogen cyanide. Hydrogen chloride. Ketones. Ethers. Esters.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Eye Contact Causes serious eye irritation.

Skin Contact May be harmful in contact with skin. Causes skin irritation.

Inhalation Harmful if inhaled.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Wood Dust Particles 9004-34-6	> 5 g/kg (Rat)	> 2 g/kg (Rabbit)	> 5800 mg/m ³ (Rat) 4 h
Styrene 100-42-5	= 1000 mg/kg (Rat)	-	= 11.7 mg/L (Rat) 4 h
Calcium stearate 1592-23-0	> 10 g/kg (Rat)	-	-
Zinc Stearate 557-05-1	> 10 g/kg (Rat)	> 2000 mg/kg (Rabbit)	> 200 mg/L (Rat) 1 h
Titanium(IV) Oxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Wood Dust Particles 9004-34-6		Group 1	Known	X
Styrene 100-42-5		Group 2B	Reasonably Anticipated	X
Titanium(IV) Oxide 13463-67-7		Group 2B		X

Legend

IARC (International Agency for Research on Cancer)
 Group 2B - Possibly Carcinogenic to Humans
NTP (National Toxicology Program)
 Known - Known Carcinogen
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Reproductive toxicity Suspected of damaging fertility or the unborn child.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2,984.40 mg/kg
ATEmix (dermal) 4,923.30 mg/kg
ATEmix (inhalation-gas) 1,788.00 mg/L
ATEmix (inhalation-dust/mist) 4.26 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Styrene 100-42-5	0.15 - 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.72: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.4: 72 h Pseudokirchneriella subcapitata mg/L EC50	3.24 - 4.99: 96 h Pimephales promelas mg/L LC50 flow-through 58.75 - 95.32: 96 h Poecilia reticulata mg/L LC50 static 19.03 - 33.53: 96 h Lepomis macrochirus mg/L LC50 static 6.75 - 14.5: 96 h Pimephales promelas mg/L LC50 static	3.3 - 7.4: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Styrene 100-42-5	2.95
Zinc Stearate 557-05-1	1.2

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable
Zinc Stearate 557-05-1	Toxic

14. TRANSPORT INFORMATION

- Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
- DOT** Not regulated
- IATA** Not regulated
- IMDG** Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Calcium Carbonate	X	X	X	X	X	X	X	X
Wood Dust Particles	X	X	X	X	X	X	X	X
Fiberglass (Fibrous Glass)	X	X	X	X	X	X	X	X
Styrene	X	X	X	X	X	X	X	X
Calcium stearate	X	X	X	X	X	X	X	X
Zinc Stearate	X	X	X	X	X	X	X	X
1,3-butadiene-styrene block polymer	X	X		X	X	X	X	X
Titanium(IV) Oxide	X	X	X	X	X	X	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 313

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Styrene - 100-42-5	100-42-5	10-20	0.1
Zinc Stearate - 557-05-1	557-05-1	<1	1.0

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene	1000 lb			X
Zinc Stearate		X		

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Wood Dust Particles - 9004-34-6	Carcinogen
Styrene - 100-42-5	Carcinogen
Titanium(IV) Oxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Wood Dust Particles 9004-34-6	X	X	X
Styrene 100-42-5	X	X	X
Zinc Stearate 557-05-1	X	X	X
Titanium(IV) Oxide 13463-67-7	X	X	X

EPA Formaldehyde Standards

CARB Phase 2 Compliant: All composite wood products or finished goods being sold/delivered comply with the applicable formaldehyde emission level for CARB Phase 2.

TSCA Title VI Compliant: All composite wood products or finished goods being sold/delivered comply with the applicable formaldehyde emission levels for TSCA Title VI.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards Not determined	Flammability Not determined	Physical hazards Not determined	Personal Protection Not determined

Issue Date: 04-Dec-2004
 Revision Date: 13-Jul-2018
 Revision Note: Regulatory review

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet